#### Instructions

**Annual Small Boat Evaluation (ASBE)** is an inspection conducted by Vessel Operations Coordinator (VOC), Commanding Officer (CO), or designee(s). All boats shall be inspected annually.

- The ASBE checklist has been condensed from the detailed ASBE outline for use with motorized Class A, I
  or II vessels. Evaluators shall use the checklists during the inspection, and shall refer to the outline for
  additional details as needed. Evaluators are responsible for all information contained within the ASBE
  outline.
  - NOTE: simple class A and I boats with portable outboard motors may use NF 57-19-05 instead of NF 57-19-01
- The ASBE outline and checklist are based on NAO 209-125, The NOAA Small Boat Standards and Procedures Manual (SBSPM), 46 CFR, 33 CFR, NFPA 302, MARPOL, ABYC standards and recommendations, United States Coast Guard (USCG) inspection criteria, and standard marine survey practices.

**Small Boat Examination (SBEX)** is an examination conducted by the Small Boat Program or a certified Marine Surveyor. Class A and I boats shall be examined every three (3) years and Class II boats shall be examined every two (2) years.

- Some items may not apply to all boats. Evaluators are responsible for determining applicability. Consult the SBSPM for equipment carriage requirements. Installed equipment in excess of requirements must be maintained to inspection standards.
- Completed evaluation checklists, reports, records of findings, and recommendations shall be signed by
  the evaluator or surveyor; signed and retained by the VOC. The completed evaluation should be
  uploaded into the Vessel Inventory Management (VIM) program and signed by the LOSBO.
- Contact the SBP Inspection Coordinator for additional guidance.

| Inspection Type               |                                 |                              |              |                 |          |
|-------------------------------|---------------------------------|------------------------------|--------------|-----------------|----------|
| Annual Small Boat             | ☐ Small Boat Examination (SBEX) |                              |              |                 |          |
| Vessel Information            |                                 |                              |              |                 |          |
| NAME of VESSEL                |                                 | VESSEL OWNER                 |              |                 |          |
| VESSEL PRIMARY OPERATING AREA | A                               | VESSEL MISSION / PRIMARY USE |              |                 |          |
| NOAA HULL REGISTRATION NUMB   | ER HULL MATERIAL                |                              | HULL TYPE    |                 |          |
| YEAR VESSEL BUILT             | VESSEL MANUFACTURER             |                              | VESSEL MODE  | L               |          |
| YEAR ENGINE(S) BUILT          | ENGINE(S) MAKE                  |                              | ENGINE(S) MO | DDEL            |          |
| TOTAL PROPULSION HORSEPOWER   | FUEL TYPE                       | FUEL CAPACITY                |              | AC/DC POWER     |          |
|                               |                                 | Gall                         | ons          |                 |          |
| LENGTH OVERALL (LOA)          | VESSEL BEAM                     | VESSEL DRAFT                 |              | VESSEL WEIGHT   | estimate |
| Feet Inches                   | Feet Inches                     | Feet Inches                  |              | Pounds          | actual   |
| Vessel Evaluation             |                                 |                              |              |                 | · ·      |
| EVALUATOR NAME                | EVALUATION LOCATION             | PRIOR EVALUATIO              | N DATE       | EVALUATION DATE |          |

3.9

Ring buoy/cushion (condition)

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |
|----------------|---------------------|-----------------|
|                |                     |                 |

| Task 1  | - Required Documentation   | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|---------|--|-------------------|---------------------|-------------------|----------|
| Class A | A, I, and II   | ,                 |                     |                   |          |
| 1.1     | Records of previous inspections and examinations   |                   |                     |                   |          |
| 1.2     | Weight tracking log <u>REQUIRED FOR ALL NOAA VESSELS</u> (Note any newly installed equipment and/or modifications) |                   |                     |                   |          |
| 1.3     | Baseline and mission risk assessments complete and updated by VOC REQUIRED FOR ALL NOAA VESSELS                    |                   |                     |                   |          |
| 1.4     | Small Boat Operators Manual updated and complete (SBOM) REQUIRED FOR ALL NOAA VESSELS                              |                   |                     |                   |          |
| 1.5     | Records of vessel drills REQUIRED FOR ALL NOAA VESSELS   |                   |                     |                   |          |
| 1.6     | Crew Qualification letters NF 57-19-04 for all operators/crewmembers <u>REQUIRED FOR ALL NOAA</u> <u>VESSELS</u>   |                   |                     |                   |          |
| 1.7     | Vessel entered into Vessel Inventory Management System (VIMS) <u>REQUIRED FOR ALL NOAA VESSELS</u>                 |                   |                     |                   |          |
| Task 2  | - Stability  | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
| Class A | A, I, and II   |                   | •                   |                   |          |
| 2.1     | Vessel operating in compliance with SBSPM Section 9,<br>"Stability, Design, and Construction Considerations"       |                   |                     |                   |          |
| 2.2     | Boat operating within defined operating capacity within the Small Boat Operations Manual (SBOM)                    |                   |                     |                   |          |
| Task 3  | - Life Saving and Emergency Equipment  | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
| Class A | A, I, and II   |                   | •                   |                   |          |
| 3.1     | Personal flotation devices (PFDs) (number, type, condition, spare carbon dioxide cartridges, re-arm kits)          |                   |                     |                   |          |
| 3.2     | Visual distress signals (number, type, condition, USCG approved)   |                   |                     |                   |          |
| 3.3     | First-Aid kit and Bloodborne Pathogen kit (adequate, all items within expiration date, properly stowed, labeled)   |                   |                     |                   |          |
| 3.4     | EPIRB/PEPIRB (registration, battery, hydro release, test)  |                   |                     |                   |          |
| 3.5     | Secondary means of communication as required:<br>Cell/satellite phone (check battery, test, operate)               |                   |                     |                   |          |
| 3.6     | Emergency sound signal (condition, audible at 0.5 nm)  |                   |                     |                   |          |
| 3.7     | Liferaft, readily accessible, hydrostatic release (if float free), serviced annually, sufficient capacity          |                   |                     |                   |          |
|         | rice), serviced armually, sufficient capacity  |                   |                     |                   |          |
|         | A and I only   |                   |                     |                   |          |
|         |  |                   |                     |                   |          |

NOAA Form 57-19-01 (9-18) Page 3 of 10 U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |
|----------------|---------------------|-----------------|
|                |                     |                 |

| Task 4  | - Fire Protection  | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|---|--|-------------------|---------------------|-------------------|----------|
| Class A   | , I, and II  | 1                 |                     |                   |          |
| 4.1   | Portable fire extinguishers (number, type, expiry, condition, secured in bracket)  |                   |                     |                   |          |
| Class I   | and II only  |                   |                     | l                 |          |
| 4.2   | Fixed system (installed IAW (VIB) 01-10, service report/expiry, condition, indicators, instructions posted)  |                   |                     |                   |          |
| 4.3   | Fixed system engine(s) automatic shutdowns tested, ventilation blower shuts down with engine shutdown  |                   |                     |                   |          |
| 4.4   | Ventilation (vent ducts, bilge blower operation, duct hose and duct closures present and operational   |                   |                     |                   |          |
| 4.5   | Backfire flame arrestor, drip pan (non-outboard gas engines)   |                   |                     |                   |          |
| 4.6   | Fire hazards minimized (excess combustibles removed, unnecessary flammables removed and stored ashore)   |                   |                     |                   |          |
| Tack 5  | – Ventilation  | Satis-            | Unsatis-            | Not               | Comments |
|   | and II only  | factory           | factory             | Applicable        | Comments |
| 5.1   | Adequate in all interior spaces  |                   |                     |                   |          |
| 5.2   | Water tank and other non-fuel tank vents (condition)   |                   |                     |                   |          |
| 5.3   | Carbon monoxide detector installed in enclosed personnel spaces  |                   |                     |                   |          |
| Tools C   | Navigation and Floatnania Facilianeant   | Satis-            | Unsatis-            | Not               | Commonts |
|   | - Navigation and Electronic Equipment  | factory           | factory             | Applicable        | Comments |
| Class A   | Very high frequency (VHF) radio (number, type, DSC,  |                   | 1                   |                   |          |
| 6.1   | test, battery)   |                   |                     |                   |          |
| l   |  |                   |                     |                   |          |
| 6.2   | Navigation lights (conform to current USCG Navigation Rules)   |                   |                     |                   |          |
| 6.2   | Rules) Global positioning system (GPS) (test operate, check  |                   |                     |                   |          |
| 6.3   | Rules)   |                   |                     |                   |          |
| 6.3   | Rules) Global positioning system (GPS) (test operate, check accuracy)  |                   |                     |                   |          |
| 6.3<br>Class I  | Rules) Global positioning system (GPS) (test operate, check accuracy) and II only Chart/charlet or current electronic charts (covers   |                   |                     |                   |          |
| 6.3<br>Class I a  | Rules) Global positioning system (GPS) (test operate, check accuracy) and II only Chart/charlet or current electronic charts (covers operations area, current and corrected) Magnetic compass/electronic compass (good working condition)  |                   |                     |                   |          |
| 6.3<br>Class I a<br>6.4<br>6.5  | Rules) Global positioning system (GPS) (test operate, check accuracy) and II only Chart/charlet or current electronic charts (covers operations area, current and corrected) Magnetic compass/electronic compass (good working condition)  |                   |                     |                   |          |
| 6.3<br>Class I a<br>6.4<br>6.5<br>Class II<br>6.6                               | Rules) Global positioning system (GPS) (test operate, check accuracy) and II only Chart/charlet or current electronic charts (covers operations area, current and corrected) Magnetic compass/electronic compass (good working condition) only At least one fixed VHF radio has a Maritime Mobile  | Satis-<br>factory | Unsatisfactory      | Not<br>Applicable | Comments |
| 6.3<br>Class I a<br>6.4<br>6.5<br>Class II<br>6.6                               | Rules) Global positioning system (GPS) (test operate, check accuracy) and II only Chart/charlet or current electronic charts (covers operations area, current and corrected) Magnetic compass/electronic compass (good working condition) only At least one fixed VHF radio has a Maritime Mobile Service Identity (MMSI) registration and integrated GPS  |                   |                     |                   | Comments |
| 6.3<br>Class I a<br>6.4<br>6.5<br>Class II<br>6.6                               | Rules) Global positioning system (GPS) (test operate, check accuracy) and II only Chart/charlet or current electronic charts (covers operations area, current and corrected) Magnetic compass/electronic compass (good working condition) only At least one fixed VHF radio has a Maritime Mobile Service Identity (MMSI) registration and integrated GPS — Ground Tackle  |                   |                     |                   | Comments |
| 6.3<br>Class I a<br>6.4<br>6.5<br>Class II<br>6.6<br>Task 7                     | Rules) Global positioning system (GPS) (test operate, check accuracy) and II only Chart/charlet or current electronic charts (covers operations area, current and corrected) Magnetic compass/electronic compass (good working condition) only At least one fixed VHF radio has a Maritime Mobile Service Identity (MMSI) registration and integrated GPS  — Ground Tackle , I (optional), and II (required) Anchor (anchor and rode condition, sufficient for             |                   |                     |                   | Comments |
| 6.3<br>Class I a<br>6.4<br>6.5<br>Class II<br>6.6<br>Task 7 -<br>Class A<br>7.1 | Rules) Global positioning system (GPS) (test operate, check accuracy) and II only Chart/charlet or current electronic charts (covers operations area, current and corrected) Magnetic compass/electronic compass (good working condition) only At least one fixed VHF radio has a Maritime Mobile Service Identity (MMSI) registration and integrated GPS  — Ground Tackle , I (optional), and II (required) Anchor (anchor and rode condition, sufficient for operations) |                   |                     |                   | Comments |

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |
|----------------|---------------------|-----------------|
|                |                     |                 |

| Task 7 | - Ground Tackle (continued)                           | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|--------|---|-------------------|---------------------|-------------------|----------|
| 7.5    | Chain locker, hawse pipe, anchor platform (condition) |                   |                     |                   |          |

| Task 8   | – Hull, Deck, Fittings and Watertight Integrity   | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|----------|---|-------------------|---------------------|-------------------|----------|
| Class A  | , l, and II   |                   |                     |                   |          |
| 8.1      | Scuppers, freeing ports (unobstructed, correctly sized)   |                   |                     |                   |          |
| 8.2      | Interior structure (open all accessible compartments (free of debris and standing water)          |                   |                     |                   |          |
| 8.3      | Fiberglass hulls (delamination, blistering, moisture, cracks)                                     |                   |                     |                   |          |
| 8.4      | Metal hulls (corrosion, pitting, deformation, fractures)  |                   |                     |                   |          |
| 8.5      | Rigid-hulled inflatable boats (RHIBs) (collar condition, chamber integrity, relief valves, leaks) |                   |                     |                   |          |
| 8.6      | Lifting equipment (labeled with Working Load Limit (WLL), OSHA Quadrennial > 200 WLL, condition)  |                   |                     |                   |          |
| Class I  | and II only   |                   | 1                   | ,                 |          |
| 8.7      | Hinged watertight doors (tight seal, gasket condition)  |                   |                     |                   |          |
| 8.8      | Watertight bulkheads (intact, watertight, penetrations)   |                   |                     |                   |          |
| 8.9      | Deck openings and thru-hulls (gasket and dog condition)   |                   |                     |                   |          |
| 8.10     | Windows (weather tight, operate freely, condition)  |                   |                     |                   |          |
| 8.11     | Keel bolts, transducers, grounding plate, stabilizers   |                   |                     |                   |          |
| Class II | only (if installed)   |                   |                     |                   |          |
| 8.12     | Remote control valves (operable, labeled, condition)  |                   |                     |                   |          |

| Task 9 | 9 – Accommodation Spaces and Equipment                            | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|--------|---|-------------------|---------------------|-------------------|----------|
| Class  | l and II only   |                   |                     |                   |          |
| 9.1    | Heaters (thermal shut off, installation, condition)               |                   |                     |                   |          |
| 9.2    | Air Conditioning units (installation, condition, capacity)        |                   |                     |                   |          |
| Class  | II only   |                   |                     |                   |          |
| 9.3    | Common and berthing spaces (condition, fire hazards, ventilation) |                   |                     |                   |          |
| 9.4    | Food <u>service</u> areas (sanitary, locking devices, condition)  |                   |                     |                   |          |

| Task 10 | ) – Marine Sanitation                      | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|---------|--|-------------------|---------------------|-------------------|----------|
| Class A | Class A, I, and II (if installed)          |                   |                     |                   |          |
| 10.1    | Toilet facilities (operable, sanitary)     |                   |                     |                   |          |
| 10.2    | Manufacturer's nameplate present on device |                   |                     |                   |          |
| 10.3    | Instructions and warnings posted           |                   |                     |                   |          |

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |
|----------------|---------------------|-----------------|
|                |                     |                 |

| Task 10 | – Marine Sanitation (continued)                 | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|---------|---|-------------------|---------------------|-------------------|----------|
| 10.4    | Chemical and sewage level indicators (operable) |                   |                     |                   |          |
| 10.5    | Verify loss of power does not allow discharge   |                   |                     |                   |          |
| 10.6    | Verify vents free and open                      |                   |                     |                   |          |
| 10.7    | System components (installation, condition)     |                   |                     |                   |          |

| Task 11 | 1 – Outboard Engines   | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |  |  |
|---------|--|-------------------|---------------------|-------------------|----------|--|--|
| Class A | Class A, I, and II (if installed)  |                   |                     |                   |          |  |  |
| 11.1    | General condition (damage, excessive oil, dirt, corrosion)   |                   |                     |                   |          |  |  |
| 11.2    | Belts and filters (condition, filters replaced annually, dated)  |                   |                     |                   |          |  |  |
| 11.3    | Oil (condition, level, test if needed)   |                   |                     |                   |          |  |  |
| 11.4    | Lower unit (general condition, damage, oil changed annually or 100 hrs)                                  |                   |                     |                   |          |  |  |
| 11.5    | Engine horsepower within limits listed on capacity plate and documented in SBOM and weight tracking log  |                   |                     |                   |          |  |  |
| 11.6    | Throttle has noticeable detent when shifted into neutral, start in gear protection, engine kill lanyards |                   |                     |                   |          |  |  |
| 11.7    | Engine controls, gauges, indicators (function normally)  |                   |                     |                   |          |  |  |
| 11.8    | Operational test (all gears and speeds)  |                   |                     |                   |          |  |  |

| Task 12   | - Inboard Engines  | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |  |  |  |
|-----------|--|-------------------|---------------------|-------------------|----------|--|--|--|
| Class I a | Class I and II (if installed)  |                   |                     |                   |          |  |  |  |
| 12.1      | General condition (damage, excessive oil, dirt, corrosion)                         |                   |                     |                   |          |  |  |  |
| 12.2      | Belts and filters (condition, filters replaced annually, dated)                    |                   |                     |                   |          |  |  |  |
| 12.3      | Engine oil (condition, level, test if needed)                                      |                   |                     |                   |          |  |  |  |
| 12.4      | Hydraulic oil (condition, level, test if needed)                                   |                   |                     |                   |          |  |  |  |
| 12.5      | Cooling system (piping, hoses, strainers, filters, clamps)                         |                   |                     |                   |          |  |  |  |
| 12.6      | Coolant (condition, level, mixture, test if needed)                                |                   |                     |                   |          |  |  |  |
| 12.7      | Exhaust system (piping, lagging, leaks, corrosion, proximity to combustibles)      |                   |                     |                   |          |  |  |  |
| 12.8      | Fuel piping, hoses and fittings (leaks, chafing, condition)                        |                   |                     |                   |          |  |  |  |
| 12.9      | Engine foundation (fatigue, stress fractures, flexing)                             |                   |                     |                   |          |  |  |  |
| 12.10     | Intakes and vents (unobstructed, clean, screened)                                  |                   |                     |                   |          |  |  |  |
| 12.11     | Machinery guards (installed over exposed gears, belts or other rotating machinery) |                   |                     |                   |          |  |  |  |

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |  |
|----------------|---------------------|-----------------|--|
|                |                     |                 |  |

| Task 12 | ? – Inboard Engines (continued)  | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|---------|--|-------------------|---------------------|-------------------|----------|
| 12.12   | Starter wiring (supported, chafing, proximity to moving parts, positive terminals/connections booted)      |                   |                     |                   |          |
| 12.13   | Seacocks and strainers (unobstructed, operable)  |                   |                     |                   |          |
| 12.14   | Transmission fluid (level, condition)  |                   |                     |                   |          |
| 12.15   | Controls and indicators (operate normally, condition)  |                   |                     |                   |          |
| 12.16   | Alternator (marine type, cleanliness, belt tension and condition, connections free of corrosion and tight) |                   |                     |                   |          |
| 12.17   | Engine shutdown at operators console (test operate)  |                   |                     |                   |          |
| If boat | is straight inboard  |                   |                     |                   |          |
| 12.18   | Propeller and shaft (prop free of damage, shaft cracks, wear, seals/stuffing box)                          |                   |                     |                   |          |
| If boat | is Inboard/Outboard (including jets)   |                   |                     |                   |          |
| 12.19   | Propeller - Jet impeller, lower unit, boot or jet drive, bucket(s) (condition, damage)                     |                   |                     |                   |          |
| If boat | is outboard  |                   |                     |                   |          |
| 12.20   | Propeller and Tilt/prop free of damage, trim motor operational   |                   |                     |                   |          |
| Task 13 | S – Fuel System  | Satis-            | Unsatis-            | Not               | Comments |

| Task 1  | 3 – Fuel System  | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |  |
|---------|--|-------------------|---------------------|-------------------|----------|--|
| Class A | Class A, I, and II   |                   |                     |                   |          |  |
| 13.1    | Integral fuel tank (condition, fill hoses double clamped)                            |                   |                     |                   |          |  |
| 13.2    | Flexible non-metallic hoses (approved type, condition, IAW ABYC H-24, H-32)          |                   |                     |                   |          |  |
| 13.3    | Fuel gauging (appropriate method, gauge, graduated ruler)                            |                   |                     |                   |          |  |
| 13.4    | Tank vents and fuel supply shut-off valves (unobstructed, labeled, operate properly) |                   |                     |                   |          |  |
| 13.5    | Filters (replaced at least annually, dated or recorded)                              |                   |                     |                   |          |  |
| 13.6    | All tanks and pipes bonded to common ground (independent integral tanks)             |                   |                     |                   |          |  |

| Task 14 | 1 – Steering System  | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |  |
|---------|--|-------------------|---------------------|-------------------|----------|--|
| Class A | , I, and II  |                   |                     |                   |          |  |
| 14.1    | Foundations/mounting bolts (condition, intact, secure)       |                   |                     |                   |          |  |
| 14.2    | Control linkages, linkage pins, ram guides (condition)       |                   |                     |                   |          |  |
| 14.3    | Potential single point system failure items (condition)      |                   |                     |                   |          |  |
| 14.4    | Locking devices (e.g., cotter pins) on all vital connections |                   |                     |                   |          |  |
| 14.5    | Seal condition, reservoir level, steering system play        |                   |                     |                   |          |  |
| Class I | Class I and II only  |                   |                     |                   |          |  |
| 14.5    | Pipes, runs, and brackets subject to vibration damage        |                   |                     |                   |          |  |

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |
|----------------|---------------------|-----------------|
|                |                     |                 |

| Task 14  | 1 – Steering System (continued)                          | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|----------|--|-------------------|---------------------|-------------------|----------|
| Class II | only   |                   |                     |                   |          |
| 14.6     | Emergency steering procedure if single engine inboard    |                   |                     |                   |          |
| 14.7     | Rudder (stock, bearing, support, packing, wear, leakage) |                   |                     |                   |          |
| 14.8     | Motor controller and gear boxes (wiring, condition)      |                   |                     |                   |          |
| 14.9     | Pumps, motors, and couplings (condition, excess play)    |                   |                     |                   |          |
| 14.10    | Hydraulics (hoses, connections, reservoir full)          |                   |                     |                   |          |

| Task 1   | 5 – Bilge System   | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|----------|--|-------------------|---------------------|-------------------|----------|
| Class I  | and II only  |                   |                     |                   |          |
| 15.1     | All standing water drains to bilge suction(s)  |                   |                     |                   |          |
| 15.2     | Pump strainers (good condition, unobstructed, bilge space clean)   |                   |                     |                   |          |
| 15.3     | Bilge pumps installed in bilges with thru-hull openings below the waterline or compartments with nonwatertight decks |                   |                     |                   |          |
| 15.4     | Bilge pumps installed IAW ABYC H-22  |                   |                     |                   |          |
| 15.5     | Remote pump actuators (test operate, condition, indicator light for auto operation)                                  |                   |                     |                   |          |
| 15.6     | Oily water separator filter (dated, changed at least annually)   |                   |                     |                   |          |
| 15.7     | Independent drain valves for watertight bulkheads kept closed and location labeled (if installed)                    |                   |                     |                   |          |
| 15.8     | Test bilge pump operation with water   |                   |                     |                   |          |
| Class II | only   |                   |                     |                   |          |
| 15.9     | High bilge level alarms, float switches (test operate, audible and visual alarm, sensor unobstructed)                |                   |                     |                   |          |

| Task 1 | 6 – Potable Water System  | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|--------|---|-------------------|---------------------|-------------------|----------|
| 16.1   | Entire system operable and in good repair   |                   |                     |                   |          |
| 16.2   | Filling hose (designated, labeled, storage)                                       |                   |                     |                   |          |
| 16.3   | Vents (screened, not near contaminants, unobstructed)                             |                   |                     |                   |          |
| 16.4   | Tanks (designated, clearly marked, maximum allowable water pressure not exceeded) |                   |                     |                   |          |
| 16.5   | Pressure system (pump, air fittings, condition)                                   |                   |                     |                   |          |
| 16.6   | Housekeeping around all components is adequate                                    |                   |                     |                   |          |

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |
|----------------|---------------------|-----------------|
|                |                     |                 |

| Task 17   | - Electrical System   | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|-----------|---|-------------------|---------------------|-------------------|----------|
| Class A,  | I, and II   |                   |                     |                   |          |
| 17.1      | Cables and wires (damage, condition, discoloration)   |                   |                     |                   |          |
| 17.2      | Cable and wire supports (condition, do not cause chafing)   |                   |                     |                   |          |
| 17.3      | No permanent "temporary" solutions (e.g., extension cords)  |                   |                     |                   |          |
| 17.4      | Shore power connection and cable (condition, damage)  |                   |                     |                   |          |
| 17.5      | Switchboards, junction boxes, panels, and inverters   |                   |                     |                   |          |
| 17.6      | Switches, breakers, and fuses (labeled, condition)  |                   |                     |                   |          |
| 17.7      | Over current devices accurately identified  |                   |                     |                   |          |
| 17.8      | Distribution points (ventilated, shielded from water and debris)  |                   |                     |                   |          |
| 17.9      | Instrumentation (meters) (working, calibrated)  |                   |                     |                   |          |
| 17.10     | Controls and meters (working, accurately labeled)   |                   |                     |                   |          |
| 17.11     | Batteries (condition, damage, corrosion, ventilated)  |                   |                     |                   |          |
| 17.12     | Battery terminals (connections secure, terminals covered, 4 wires mamximum attached to either terminal) |                   |                     |                   |          |
| 17.13     | Battery trays (resistant to electrolyte, condition)   |                   |                     |                   |          |
| 17.14     | Ventilation (sufficient to dissipate charging gases)  |                   |                     |                   |          |
| 17.15     | Inverter components (marine type, grounded, wire size)  |                   |                     |                   |          |
| Class I a | ind II only   |                   | 1                   |                   |          |
| 17.16     | Drip shields (present, good condition)  |                   |                     |                   |          |
| 17.17     | Lighting system (each light is protected by a lens or guard)  |                   |                     |                   |          |
| 17.18     | Outlets (properly grounded and covered/watertight)  |                   |                     |                   |          |

| Task 18 – Generator |   | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|---------------------|---|-------------------|---------------------|-------------------|----------|
| Class A             | Class A, I, and II  |                   |                     |                   |          |
| 18.1                | General condition (damage, excessive oil, dirt, corrosion)                          |                   |                     |                   |          |
| 18.2                | Belts and filters (condition, filters replaced annually, dated or records provided) |                   |                     |                   |          |
| 18.3                | Exhaust system (piping, lagging, leaks, corrosion)                                  |                   |                     |                   |          |
| 18.4                | Compartment adequately ventilated, dry as possible                                  |                   |                     |                   |          |
| 18.5                | Oil (condition, level, test if needed)  |                   |                     |                   |          |
| 18.6                | Cooling system (coolant level, coolant mix, piping, gaskets)                        |                   |                     |                   |          |

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |  |
|----------------|---------------------|-----------------|--|
|                |                     |                 |  |

| Task 18 | B – Generator (continued)                               | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|---------|---|-------------------|---------------------|-------------------|----------|
| 18.7    | Voltmeter, ammeter (if ≥ 50 volts, verify operation)    |                   |                     |                   |          |
| 18.8    | Frequency measuring device (verify operation)           |                   |                     |                   |          |
| 18.9    | Over current protection device rated at <115% full load |                   |                     |                   |          |

| Task 19            | 9 – Markings   | Satis-<br>factory | Unsatis-<br>factory | Not<br>Applicable | Comments |
|--------------------|--|-------------------|---------------------|-------------------|----------|
| Class A, I, and II |  |                   |                     |                   |          |
| 19.1               | Boat is marked in accordance with SBSPM Section 13, "Visual Identification and Registration" |                   |                     |                   |          |

| Task 20 – Validation |                |           |      |  |
|----------------------|----------------|-----------|------|--|
| 20.1                 | EVALUATOR NAME | SIGNATURE | DATE |  |
| 20.2                 | VOC/CO NAME    | SIGNATURE | DATE |  |
| 20.3                 | LOSBO NAME     | SIGNATURE | DATE |  |

| Comments: List all Category 1 deficiencies in the space below. Use the listing of common Category 1 deficiencies in VIB 02-10 for reference located in the SBP Website. |  |  |  |
|---|--|--|--|
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |

| NOAA Fo | rm 57-19-01   |
|---------|---------------|
| (0_19)  | Page 10 of 10 |

U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

| NAME of VESSEL | EVALUATION LOCATION | EVALUATION DATE |  |
|----------------|---------------------|-----------------|--|
|                |                     |                 |  |

| Additional Comments: List all Category 1 deficiencies in the space below. Use the listing of common Category 1 |  |
|--|--|
| deficiencies noted on SBP Website for a reference.   |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |